

Mechanical Key Override (MKO®)

SAFLOK™ offers the standard concealed mechanical key override (MKO®) and the optional small format interchangeable core (SFIC) MKO as specified options for its MT® lock. Using the mechanical override feature, the electronic security can be overridden to allow use of the mechanical key. The concealed element of the standard MKO is a design option that refines the aesthetic appeal of the lock.



SAFLOK MT with the standard concealed MKO. The SFIC MKO is also available in a concealed format.



SAFLOK MT with the optional SFIC MKO.

Mechanical Key Override (MKO®)

Both the standard MKO and the optional SFIC MKO have the following features:

- Enables emergency access
- Enables post-vandalism access
- Provides extended mechanical double-locking
- Meets specific cultural requirements

Notes:

1. Adding the convenience of MKO cancels the electronic safety features of a lock.
2. Arrow, Best, Falcon, InstaKey, Kaba, Keymark, KSP, and Schlage are all compatible SFIC brands.



SPECIFICATIONS

- Mortise lock available in standard function, 1" (25 mm) throw dead bolt and 3/4" (19 mm) dead locking latch bolt
- 2-3/4" from door edge to lever (backset)
- Operates on standard AA alkaline battery pack
- Door thickness range 1-3/4" – 2-1/8" for standard product

Options:

- Spacer plate available for retrofitting 1-3/8" thick doors
- Custom designs available for thicker doors
- Escutcheon: 9-3/4" (248 mm) x 3-1/2" (89 mm)
- Armored front: 8" (203 mm) x 1-1/4" (32 mm) or 8" (203 mm) x 1-1/16" (27 mm)

Certifications:

- Certified by BHMA to be in compliance with ANSI 156.13-2002 American National Standard for mortise locks and latches. Grade 1 level for both security and operational requirements
- Certified by BHMA to be in compliance with ANSI 156.25-2002 American National Standard for electrified locking devices
- Certified by Underwriters Laboratories (UL) for use on fire doors up to a three-hour rating

When ordering, specify:

- Total number of locksets and spares
- Desired finish
- Door thickness and composition (wood or metal)
- Door preparation – consult SAFFLOK for template
- Door frame composition – wood or metal frame and strike plate measurements**



**All SAFFLOK MT locks are prepared to accept standard ASA 4-7/8" (125 mm) strike plate. — Lock specifications and features may change without notice.



A Member of the Kaba Group

For worldwide office locations and contact information, visit us at

www.saflok.com.

USA • Canada

Phone: **877.272.3565**

Europe • Middle East • Africa

Phone: **33.1.30.13.04.04**

Asia

Phone: **86.10.5861.3561**

Manufactured under one or more of the following patents:

U.S.: 4,177,657; 4,411,144; 4,534,194; 4,890,870; 5,198,643; 5,477,041; 5,820,177; 5,986,564; 7,051,561; D494,841; D501,131; D512,899; D519,021; D531,629; D533,009; D533,047; D533,762; D533,763; D535,629 CANADA: 1,252,854; 1,298,902
U.K. 2,010,375
Other U.S. and foreign patents pending

SAFFLOK reserves the right to modify the characteristics and features of all products in this publication.
©2008 SAFFLOK, all rights reserved.